

Tri-Way 425x425x100mm

Ductile iron D400 hinged double triangular gully grate

A revolutionary and unique design by Wrekin gives the best solution for BS EN 124:1994 D400 gully grates in one product.

Captive hinges combine with double triangular seating to allow single unit opening with an anti-theft feature.



-  For use in a Group 3 Class D400 carriageway environment
-  All fully comply with BS EN 124:1994 and are Kitemarked by BSI
-  Complies fully with UK Highways Authority specification HA 104/09
-  A unique and patented articulated coupling links two double triangular units allowing the benefits of three point suspension together with the advantages of single unit opening
-  Captive hinges reduce theft risk whilst allowing easy lifting for gully cleaning
-  Due to the unique design, hinging is reversible allowing the grating to hinge correctly for the traffic flow direction
-  Up to 1200cm² waterway area
-  Three point suspension on covers for non-rock stability
-  Manufactured from strong and highly durable ductile iron


Wrekin product code	Clear opening size (Cx D mm)	Frame depth (mm)	Over frame size (Ax B mm)	Waterway area (cm ²)
DGHT0D4/4242/KHA	425 x 425	100	560 x 520 *	1200

* Tapers at base to 450 x 450 clear opening

Available options: Screw-locking to deter unauthorised access to the gully chamber (will require standard extended-shank socket set tooling to engage/disengage locking screw).
60+ PSRV anti-slip coating to top surface.



Illustrated: DGHT0D4/4242/KHA



1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves that the above data is current.
3. Wrekin cannot be held responsible for the performance of these products as conditions of use are beyond our control.
4. Installation details are available on request.